



HOLED AND HOLELESS JACK UNITS

Both holed and holeless jack units are available. The in-ground units include a factory-applied corrosion-preventive coating, and a one-piece buffer/pit support plate designed to reduce installation time and cost. Other features include interval leveling/aligning bolts, isolated platen plate, and bolt-on heads with one-piece packing and wiper rings. All jobs include a spare set of packing. Above-ground jack units include many of the same features. Other options include PVC liners, special cathodic protection, multi-stage telescopic jack units and double-wall cylinders.



GUIDE SHOES

- Suitable for all standard passenger elevators up to 6,000 lb. capacity on 8 lb. – 12 lb. – 15 lb. rails
- Removable nylon swivel insert
- Less costly than conventional swivel guide shoes
- No bearing or springs to wear out or break
- Easy to adjust



RAIL BRACKETS

- For 8 – 12 – 15 lb. rails
- Reduces installation time by allowing complete rail adjustment in all directions
- Available with or without hardware and wall inserts
- Wide adjustment range eliminates need to stock several different brackets
- Special rail brackets and wall inserts available upon request
- Rail brackets also available for 18½ – 22½ – 30 lb. rails



2575 GREENSBURG ROAD • NORTH CANTON, OH 44720 • PH. 330-833-3600 FAX 330-833-0229

E-Mail info@CantonElevator.com

VISIT OUR WEB SITE

<http://www.CantonElevator.com>